

Rawhide 127WL – Data sheet.



Dimensions

- Length over all: 12,55m
- Width over all: 3,25m
- Hight from waterline (to none-foldable equipment): 2,65m
- Total boat hight (from keel to top of none-foldable equipment: 3,45m
- Dry weight: 3420kg
- Fuel capacity: 2x500L.
- Maximum loading capacity (dry boat): 3350kg
- Maximum load capacity (fully fuelled and 7 passengers: 1430kg
- Maximum number of passengers: 12
- Number of seating inside: 10
- Number of seating aft deck: 2
- Suspended seats inside: 2
- Maximum kw: 515kw
- Top speed (maximum kw): 42 knots
- Sea category: C
- Hull warranty: 3 years
- Hull
- Length waterline: 9,9m
- Width waterline: 2,83m
- Deadrise aft: 18 degrees
- Deadrise centre: 18 degrees
- Deadrise bow: 31 degrees
- Type of hull: Single – Deep V
- Air-steps: Yes
- Number of steps: 3
- Hight to gunwale from waterline bow: 1,05m
- Hight to gunwale from waterline centre: 0,75m
- Hight to gunwale from waterline aft: 0,72m
- Hull thickness: 6mm
- Hull material: Aluminium
- Alloy: 5058

Deck

- *Bow deck dimensions:*
- Width bow: 1,93m
- Width aft: 2,12m
- Length lowest point: 3,91m
- Length highest point: 4,45m
- *Aft deck dimensions:*
- Highest width: 2,25m
- Highest length: 1,31m
- *Side deck dimensions:*
- Centre of cabin: 0,21m
- Forward of cabin: 0,5m
- Aft of cabin: 0,4m
- Aft deck side: 0,59m
- *Engine well dimensions:*
- Highest width: 1,88m
- Length from transom to railing: 0,7m
- Railing height from aft deck: 0,9m
- Railing height from aft side deck: 0,7m
- Railing height from bow deck: 1,46m
- Railing height from bow side deck: 0,8m
- Railing material: Aluminium
- Alloy: 6063

Cabin

- Length over all: 5,21m
- Width over all: 2,62m
- Height from aft deck (to none-foldable structures): 2,1m
- Height from bow deck (to none-foldable structures): 2,28m
- Height to roof from aft deck: 1,83m
- Height to roof from bow deck: 1,73m
- Entrance width from aft deck: 0,66m
- Entrance width from bow deck: 0,61m
- Ceiling height most forward position: 2m
- Ceiling height most aft position: 2,2m
- Material: Aluminium
- Alloy: 5058

Equipment standard:

- Hydraulic engine lift (600mm vertical lift)
- Manual toilet
- Black water deck drain
- Black water tank
- Galley with gas cooker, microwave, and sink
- Welded pollards
- Welded 40mm railings

- Radar bow cabin top
- Hardened glass
- 2pcs starting battery, GEL
- 2pcs auxiliary battery, AGM
- Heating system
- Suspended driver's seat
- Suspended navigators' seat
- Cushions in UV proof materials
- Bow thruster 12V 90kg thrust.
- Hydraulic power pack 12V
- Hydraulic 1t/m crane
- Anchor, type Bruce, 15kg.
- Diving ladder bow
- Diving ladder aft
- Bilge pumps, Electric automatic
- Bilge pumps, manual
- Navigation system with 4 pcs 12" plotter
- Electronic main switch controlled from drivers' position.
- Digital battery insulator
- USB ports 4pcs
- Automatic interceptors
- Hull
- Antifouling with 6-layer primer
- Painted anti slip-on deck surfaces
- Lockable hatches (padlock)
- -Anchor
- Bruce 15kg anchor
- -Ladders
- Diving ladder bow and aft with MOB function
- -Seats
- Suspended driver & navigator seats
- Adjustable width, length, armrest
- -Cabin
- Rubber suspended cabin.
- Detachable oil resistant rubber floor in cabin
- Extendable navigation table
- Dividable bilge box
- -Fire equipment
- 2pcs 6kg fire extinguishers aft in cabin
- 230v sockets in cabin
- IP68 230v socket on bow deck
- -Shore power
- Shore power indicator on targa bow (blue light)
- 230v defroster
- Diesel defroster
- -Lighting
- Working lights bow deck.
- Deck light bow
- Diving ladder light aft deck
- Extra working lights forward
- Manual search lights 2pcs
- Side work lights 6pcs



Victum Marine AB
559029-8096
SE559029809601

Södra Kustvägen 501
761 41 Norrtälje
Stockholms Län

www.victumboats.se
info@victumboats.se

